



### Deckellager DIN 505 L mit 2 Anschraublöchern

$d_1$ D10	$a$	$b_1$ 0-0,3	$b_2$ 0-0,1	$b_3$	$c$	$d_2$ mm	$d_6$	$d_7$	$d_8$	$h_1$ +/- 0,2	$h_2$ max.	$m_1$	$m_2$
25	165	45	35	40	22	35	15	M12	M10	40	85	125	65
30	165	45	35	40	22	40	15	M12	M10	40	85	125	65
35	180	50	40	45	25	45	15	M12	M10	50	100	140	75
40	180	50	40	45	25	50	15	M12	M10	50	100	140	75
45	210	55	45	50	30	55	19	M16	M12	60	120	160	90
50	210	55	45	50	30	60	19	M16	M12	60	120	160	90
55	225	60	50	55	35	65	19	M16	M12	70	140	175	100
60	225	60	50	55	35	70	19	M16	M12	70	140	175	100
70	270	65	53	60	40	85	24	M20	M16	80	160	210	120
80	290	75	63	70	45	95	24	M20	M16	90	180	230	130
90	330	85	73	80	50	105	28	M24	M20	100	200	265	150
100	355	95	81	90	55	115	28	M24	M20	110	220	290	170
110	355	95	81	90	55	125	28	M24	M20	110	220	290	170
125	420	110	94	100	60	145	35	M30	M24	130	260	340	200
140	440	125	105	120	65	160	35	M30	M24	150	300	360	220